

What is claimed is:

1. A label form comprising:
a backing member;
a label member removably attached to a first side of the backing member;
and
a transparent laminate removably attached to a second side of the backing member;
wherein the label member and the transparent laminate are independently removable from the backing member.
2. The label form of claim 1, wherein the label member includes a top side adapted for being printed on.
3. The label form of claim 1, wherein the backing member includes a first section and a second section separated by a split-line and wherein the label member and the transparent laminate each straddle the split-line.
4. The label form of claim 3, wherein the label member and the transparent laminate adhere to different sections of the backing member when the backing member is separated along the split-line.
5. The label form of claim 3, wherein the label form further includes a first shaped edge adapted for aligning the label member to a stock member and a second shaped edge adapted for aligning the laminate to the stock member.
6. The label form of claim 1, wherein the transparent laminate includes a clear plastic.

7. The label form of claim 1, wherein the backing member includes a release coating on both major surfaces.
8. A label form comprising:
 - a backing member having a first side and a second side;
 - a label member having a surface adapted for being printed upon, the label member removably attached to the backing member; and
 - a transparent laminate removably attached to the backing member and located on the backing member so that the transparent laminate does not cover the label member surface adapted for being printed on.
9. The label form of claim 8, wherein the label member is located on the first side and the transparent laminate is located on the second side of the backing member.
10. The label form of claim 8, wherein the label member and the transparent laminate are both located on the first side of the backing member.
11. The label form of claim 8, wherein the backing member includes a split-line.
12. The label form of claim 8, wherein the transparent laminate member is wider than the label member.
13. The label form of claim 12, wherein the transparent laminate member is approximately 1/4" wider than the label member.
14. A label form comprising:
 - a backing member having a first section and a second section separated by a split-line;

a label member removably attached to one side of the backing member and located over the split-line; and

a transparent laminate removably attached to a second side of the backing member and located over the split-line, wherein the label member and the transparent laminate are located on the backing member so that when the backing member is separated along the split-line the transparent laminate and the label member adhere to different sections of the first and second sections of the backing member.

15. The label form of claim 14, wherein the label member is located on the first side and the transparent laminate is located on the second side of the backing member.

16. The label form of claim 14, wherein the transparent laminate member is wider than the label member.

17. The label form of claim 14, wherein the label form further includes a first shaped edge adapted for aligning the label member to a stock member and a second shaped edge adapted for aligning the laminate to the stock member.

18. A method of applying a label to a stock member, the method comprising:
removing a label member from a backing member and applying the label member to the stock member; and

separately removing a transparent laminate from the backing member and applying the transparent laminate over the label member.

19. The method of claim 18, wherein removing the label member includes separating the backing member along a split-line, wherein the label member adheres

to a first section of the backing member and the transparent laminate adheres to a second section of the backing member.

20. The method of claim 19, further comprising aligning the label member to the stock member using an alignment feature on the first section of the backing member and aligning the transparent laminate to the stock member using a second alignment feature on the second section of the backing member.

21. The method of claim 18, further comprising printing on the label member before removing the label member from the backing member.